



ELECTRICAL SPECIFICATIONS

Frequency Range: 2.4-2.48/5.15-5.85/6-7.125 GHz
 Gain: 6/6/6 dBi
 Polarization: Vertical
 Horizontal Beamwidth: 105°/105°/105°
 Vertical Beamwidth: 85°/60°/50°

VSWR: $\leq 1.5:1$, max 2.0
 Isolation: >30 dB
 Impedance: 50 Ω
 Lightning Protection: None
 Max Input Power: 50 W per port



MECHANICAL SPECIFICATIONS

Dimensions: 15.35"x15.35"x2.16" (390x390x55mm)
 (300x300x60mm)
 Weight: 1.5 lb (0.68 kg)
 Installation: Flush Mount to Wall or Articulating Mount
 (included)

Radome Material: ABS
 Connector: N-Style
 Number of Leads: 8
 Cable Length: 36" (910mm)
 Cable Type: ATS-200



ENVIRONMENTAL SPECIFICATIONS

Installation Environment: Indoor/Outdoor
 Operating Temperature: -40 to 158°F (-40 to 70°C)
 Wind Velocity: 134 mph (216 km/h)
 IP Rating: IP66

WARRANTY

2 Year Limited Warranty



HORIZONTAL

VERTICAL

